

UNIQUE MODE OF ACTION

At moisture contents generally in the range 25% to 50% a high level of protection was afforded by the test treatment within three months. Only a few of the test blocks, which were taken from the areas most remote from the source of boron, were unprotected.

At higher moisture contents, protection was achieved more quickly and the test samples were essentially fully protected after three months.

There was evidence of continued distribution of the boron after the storage periods.

In view of the slow rate of attack generally experienced in the practical situation, it is considered that the system of applying boron-based fungicides is likely to provide protection in practice if applied to joist ends, which are at risk of decay

(Building Research Establishment BRE)

USING THE PRODUCT

Preparation - Injection Treatment

Holes should be angle drilled at no more than 4" (100mm) centres just short of the full depth of the vulnerable timber and Boracol 40/1 Wood Preservative Gel injected to fill these 'reservoirs'. Holes should be plugged using timber dowels or other suitable plugs.

OTHER INFORMATION

Cleaning Equipment - Ordinary tap water with clean tools, equipment and spillages.

LD₅₀ - 8000mg/kg body weight (Rat - Wistar)

Shelf Life - Correctly stored, the product has a shelf life of twelve months.

Safety Recommendations - Read and understand full SDS information before use. Do not swallow. Protect eyes and skin. Keep away from children, animals, foodstuff and drink. Store safely in original containers ensuring that they are tightly sealed. Keep in a cool place but do not allow the product to freeze.

Standard Packaging - 400cc Cartridge

Boracol B40/1 Gel is approved for use as directed under the Control of Pesticide Regulation 1986 (HSE No: 6133) for professional use only.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice, please ensure you have the latest updated information.

Channelwood Preservations Limited
13 Clayhill Industrial Park
Neston
South Wirral
Cheshire
CH64 3UG

Telephone: (0151) 342 3728
Fax: (0151) 342 9472
e-mail: info@channelwood.co.uk